



iBR iTC iS S³ CLCS

Specifications

DIMENSIONS

Length.....	139" / 354 cm
Width.....	48" / 122 cm
Height.....	43.9" / 111.4 cm
Weight (dry).....	980 lb. / 446 kg
Rider capacity.....	3
Fuel capacity.....	18.6 US gal / 70 l
Storage capacity.....	16.4 US gal / 62 l

ENGINE

Type.....	1503 XHO Rotax® 4-TEC® engine
Intake system.....	Supercharged with external intercooler, 60 mm throttle body
Bore x stroke.....	100 mm x 63.4 mm
Displacement.....	1,494 cc
Compression ratio.....	8.4:1
Cooling.....	Closed-loop cooling system (CLCS)
Fuel type.....	87 octane – minimum 91 octane – recommended

DRIVE UNIT

Propulsion system.....	Sea-Doo® Direct Drive
Jet pump.....	Aluminium, axial flow, single stage, large hub with 10-vane stator
Transmission.....	iBR
Impeller.....	Stainless steel

ELECTRICAL

Ignition.....	Digital induction
Starter.....	Electric
Battery.....	12 V

HULL AND COMPONENTS

Type.....	S ³ Hull™
Colour.....	Pearl White*



Tilt steering with information centre



Reboarding platform with storage



Touring seat



iBR™ (Intelligent Brake & Reverse) brake lever



Speed Tie™



Glove box organiser

Standard Features

GTX LIMITED iS 260

HULL AND COMPONENTS

iControl™	The “Brain” that integrates and controls all systems to create the best possible ride.
iS™	Allows the hull to move independently of the upper deck, isolating rider and passenger from the impact of rough water. Electronic adjustment, manual or automatic mode. Auto docking position, Touring calibration.
S ³ Hull	Stepped, stable & strong. Lightweight material, ribbed and stepped. Creates a low-pressure zone to reduce drag for nimble handling and rail-tight cornering.
Touring / Sport mode	Offers a choice between two throttle responses for different riding styles. Touring mode is the default setting offering a more progressive acceleration curve for a more confident ride – ideal for cruising and 2-up riding. Sport mode can be easily activated using the Set button. It provides all acceleration performance for a more aggressive throttle response.
Hinged seat	Easy-open seat with convenient stay-open support struts. Provides easy access to the engine compartment while remaining attached to the watercraft.
Touring seat	Ergonomically designed for comfort and great looks providing ultra-plush seating for three.
High-performance electric VTS™ (Variable Trim System)	Provides pre-set positions for quick settings when adjusting boat trim, maximises acceleration and high-speed stability.
Bow and stern eyes	Designed for towing or securing the craft to a trailer or dock.
Carpeted footwells and deck pads	Offer extra comfort, non-skid surface and great looks.
Reboarding platform with rear storage	Easy access to battery, fuses and storage.
Fold-down reboarding step	Makes reboarding from the water easier and quicker.
Ski tow eye	For easy and secure attachment of ski rope.
Watertight, removable storage bin	Provides dry storage for luggage and necessities with easy access.
Tilt steering	4 adjustable steering and information centre angles for maximum ease and comfort.
Interactive Multifunction Digital Information Centre	Reports 34 key operating functions: Fuel level, Tachometer, Speedometer, Hour meter, Compass, Clock, Fuel consumption meter, Time / Distance to empty, Altitude, Water temperature, Depth finder, Touring / Sport mode, Cruise control, Slow mode, VTS, VTS preset, Suspension settings: auto and manual mode, Suspension dock mode ON_OFF, F-N-R indicator, Low fuel level, Low oil level, Low oil pressure, Low voltage, Overheat, Hi voltage, Check engine, Sensor check, Battery protection, Key (wrong key), L-Key / R-Key, Maintenance info, Error codes.
Digitally Encoded Security System (D.E.S.S.™)	Industry's first digitally encoded theft-deterrent system.
Foam flotation	Ride with security and peace of mind. Meets or exceeds USCG standards.
Off-Throttle Assisted Steering (O.T.A.S.™)	Provides the operator with additional steering effect in off-throttle situations for greater manoeuvrability.
Quick latch fuel filler design	External exhaust cooling flush attachment
Sponsons	Special comfort hand grips
Bumpers	Wide handlebars
Adjustable mirrors	Emergency floating lanyard (permanent)
Reboarding handles on rear platform	Cut & sew seat with 2 colours
Rear grab handle	Seat strap
Front splash deflector	Operator's guide, instructional video and booklet
Dual drain plugs	
Engine access cover (removable)	

OPTIONS

Removable wakeboard rack	Lap timer
Ski mode	Engine temperature
Top/average speed/RPM	Fire extinguisher

WARRANTY

BRP limited warranty covers the watercraft for one year.*

ENGINE

Supercharged, intercooled 1,494 cc four-stroke, Rotax with four valves	Supercharged, intercooled 1503 XHO Rotax 4-TEC engine provides reliable ultra-high performance in fresh or saltwater, increased torque at low RPM, optimised power at all RPM levels and throttle positions.
Multi-port fuel injection	Better control of exhaust emission and power at all RPM ranges to reduce emissions and reduce fuel consumption.
iTC™ (Intelligent Throttle Control) system	Operating electronically, this advanced throttle system starts you in neutral for easier dockside starts. It also features an activity-specific cruise control, Touring / Sport mode and Variable Trim System that can all be set to accommodate your riding style. The result is a more responsive, more intuitive ride.
iControl Learning Key™	The programmable Learning Key allows you to limit the performance of the PWC based on rider skill level. Each of the two settings can be fine-tuned using the mode/set buttons.
D-Sea-Bel™ system	Combines a series of resonators and vibration-absorbing components to make Sea-Doo watercraft some of the quietest on the water.
Closed-loop cooling system	Uses coolant to keep the engine running at the ideal temperature, much like a car's radiator. Also keeps out corrosive saltwater and debris.
Water/air separator	Provides maximum airflow to engine and reduces water intrusion.
Watertight digital ignition	Provides optimal energy for a consistent spark, ensuring maximum performance.
RPM limiter	Protects engine from over-revving.
Warning device	Warns operator of engine and exhaust overheating, engine management and system failure.
Handlebar-mounted start/stop button	Engine starts and stops with single, user-friendly control button.
Tip Over Protection System (T.O.P.S.™)	Protects engine in case of turn over.

PROPULSION SYSTEM

iBR (Intelligent Brake & Reverse) system	The world's only on-water braking system, iBR lets you stop up to 100 feet sooner than any other watercraft ¹ . All with the squeeze of a lever. And with its electronic reverse, it gives you a level of manoeuvrability that makes docking easier.
Sea-Doo Direct Drive propulsion system	Delivers optimum performance with the Rotax engine.
Replaceable UHMW**	Provides long impeller life, less maintenance wear ring and maximum thrust.
Dual automatic vacuum siphon pumps	Continuously removes water entering the engine compartment.
Large diameter drive shaft	Maintains engine and pump alignment at all operating speeds.
Stainless steel impeller	Delivers improved acceleration, higher top impeller speed and less cavitation.
Aluminium stator vanes	Handles the high-performance engine without erosion.

LIMITED PACKAGE

Additional gauge functions	Depth finder, Time/Distance to empty, Altitude.
Speed Tie™	Automatic retractable mooring lines eliminate the hassles of traditional docking lines.
Removable dry bag	Keeps contents dry and converts to backpack when removed.
Sandbag anchor	Easy way to hold your boat in one position.
Safety kit	Contains all the essential safety equipment.
Glove box organiser	Ideal to keep gear or cell phone dry; removable and watertight.
Custom boat cover	Protect your PWC.



*In some markets, the duration of the warranty coverage may differ.

©2010 Bombardier Recreational Products Inc., (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. †GTX is a trademark of Castrol Limited used under license. **Ultra-high molecular-weight polyethylene. † Traveling at 50 mph/80.47 km/h (based on BRP Internal test). Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models, accessories or options depicted herein may not be available in your region.

