



## iBR iTC S<sup>3</sup> CLCS

### Specifications

#### DIMENSIONS

Length.....	139" / 354 cm
Width.....	48" / 122 cm
Height.....	46.5" / 118.1 cm
Weight (dry).....	855 lb. / 388 kg
Rider capacity.....	3
Fuel capacity.....	15.9 US gal / 60 l
Storage capacity.....	13.7 US gal / 52 l

#### ENGINE

Type.....	1503 XHO Rotax® 4-TEC® engine
Intake system.....	Supercharged with external intercooler, 60 mm throttle body
Bore x stroke.....	100 mm x 63.4 mm
Displacement.....	1,494 cc
Compression ratio.....	8.4:1
Cooling.....	Closed-loop cooling system (CLCS)
Fuel type.....	87 octane – minimum 91 octane – recommended

#### DRIVE UNIT

Propulsion system.....	Sea-Doo® Direct Drive
Racing pump with.....	Aluminium, axial flow, single stage, high-performance intake grate
Transmission.....	iBR™
Impeller.....	Stainless steel

#### ELECTRICAL

Ignition.....	Digital induction
Starter.....	Electric
Battery.....	12 V

#### HULL AND COMPONENTS

Type.....	S <sup>3</sup> Hull™
Colour.....	Black and Dragon Red



X-Steering with A.E.S.™



X-Information centre



Special X-logo



Racing design



X-Colouration seat



Hinged seat

# Standard Features

## HULL AND COMPONENTS

High-performance electric VTS™ (Variable Trim System)	Provides pre-set positions for quick settings when adjusting boat trim, maximises acceleration and high-speed stability.
iControl™	The "Brain" that integrates and controls all systems to create the best possible ride.
S <sup>3</sup> Hull	Stepped, stable & strong. Lightweight material, ribbed and stepped. Creates a low-pressure zone to reduce drag for nimble handling and rail-tight cornering.
Touring / Sport mode	Offers a choice between two throttle responses for different riding styles. Touring mode is the default setting offering a more progressive acceleration curve for a more confident ride – ideal for cruising and 2-up riding. Sport mode can be easily activated using the Set button. It provides all acceleration performance for a more aggressive throttle response.
Hinged seat	Easy-open seat with convenient stay-open support struts. Provides easy access to the engine compartment while remaining attached to the watercraft.
Watertight, removable storage bin	Provides dry storage for luggage and necessities with easy access.
Tilt steering	4 adjustable steering and information centre angles for maximum ease and comfort.
Bow and stern eyes	Designed for towing or securing the craft to a trailer or dock.
Carpeted footwells and reboarding deck pads	Offer extra comfort, non-skid surface and an aggressive diamond-plate pattern for additional traction.
Interactive Multifunction Digital Information Centre	Reports 30 key operating functions: Fuel level, Tachometer, Speedometer, Hour meter, Compass, Clock, Fuel consumption meter, Time / Distance to empty, Top/average speed/RPM, Lap timer, Engine temperature, Water temperature, Touring / Sport mode, VTS, VTS preset, F-N-R indicator, Low fuel level, Low oil level, Low oil pressure, Low voltage, Overheat, Hi voltage, Check engine, Sensor check, Battery protection, Key (wrong key), L-Key / R-Key, Maintenance info, Error codes.
Digitally Encoded Security System (D.E.S.S.™)	Industry's first digitally encoded theft-deterrent system.
Foam flotation	Ride with security and peace of mind. Meets or exceeds USCG standards.
Off-Throttle Assisted Steering (O.T.A.S.™)	Provides the operator with additional steering effect in off-throttle situations for greater manoeuvrability.
Ski tow eye	For easy and secure attachment of ski rope.
Sponsons	Dual drain plugs
Bumpers	External exhaust cooling flush attachment
Adjustable mirrors	Special comfort hand grips
Reboarding platform	Emergency floating lanyard (permanent)
Reboarding handles on rear platform	Seat strap
Rear grab handle	Operator's guide, instructional video and booklet
Front splash deflector	

## X-PACKAGE

X-Steering with A.E.S. (Adjustable Ergonomic Steering)	The only fully adjustable handlebar in the industry. With A.E.S. the rider can adjust the handlebar width and grip for a fully customised ride.
X-Colouration seat	Race-inspired designed for comfort and great looks providing seating for three.
X-Tra traction carpet	With diamond plate pattern

## OPTIONS

3-position retractable ski pylon	Glove box organiser
Removable wakeboard rack	Safety kit
Depth finder	Sandbag anchor
Cruise control	Speed Tie™
Ski mode	Fold-down reboarding step
Slow mode	Protective cover
Altitude	Advanced TEC trailer
Removable dry bag for front storage	Fire extinguisher

## WARRANTY

BRP limited warranty covers the watercraft for one year.\*

# RXT-X 260 RS

PERFORMANCE | 2011



## ENGINE

Supercharged, intercooled 1,494 cc four-stroke, Rotax with four valves per cylinder	Supercharged, intercooled 1503 XHO Rotax 4-TEC engine provides reliable ultra-high performance in fresh or saltwater, increased torque at low RPM, optimised power at all RPM levels and throttle positions.
iTC™ (Intelligent Throttle Control) system	Operating electronically, this advanced throttle system starts you in neutral for easier dockside starts. It also features an activity-specific Touring / Sport mode and Variable Trim System that can be set to accommodate your riding style. The result is a more responsive, more intuitive ride.
iControl Learning Key™	The programmable Learning Key allows you to limit the performance of the PWC based on rider skill level. Each of the two settings can be fine-tuned using the mode/set buttons.
Multi-port fuel injection	Better control of exhaust emission and power at all RPM ranges to reduce emissions and reduce fuel consumption.
D-Sea-Bel™ system	Combines a series of resonators and vibration-absorbing components to make Sea-Doo watercraft some of the quietest on the water.
Water-cooled exhaust pipe	Regulates exhaust temperature.
Closed-loop cooling system	Uses coolant to keep the engine running at the ideal temperature, much like a car's radiator. Also keeps out corrosive saltwater and debris.
Water/air separator	Provides maximum airflow to engine and reduces water intrusion.
Watertight digital ignition	Provides optimal energy for a consistent spark, ensuring maximum performance.
RPM limiter	Protects engine from over-revving.
Warning device	Warns operator of engine and exhaust overheating, engine management and system failure.
Handlebar-mounted start/stop button	Engine starts and stops with single, user-friendly control button.
Tip Over Protection System (T.O.P.S.™)	Protects engine in case of turn over.

## PROPULSION SYSTEM

iBR (Intelligent Brake & Reverse) system	The world's only on-water braking system, iBR lets you stop up to 100 feet sooner than any other watercraft! All with the squeeze of a lever. And with its electronic reverse, it gives you a level of manoeuvrability that makes docking easier.
Sea-Doo Direct Drive propulsion system	Delivers optimum performance with the Rotax engine.
Aluminium stator vanes	Handles the high-performance engine without erosion.
Replaceable UHMW** wear ring	Provides long impeller life, less maintenance and maximum thrust.
Dual automatic vacuum siphon pumps	Continuously removes water entering the engine compartment.
Large diameter drive shaft with crowned spline design	Maintains engine and pump alignment at all operating speeds.
Stainless steel impeller	Delivers improved acceleration, higher top speed and less cavitation.



\*In some markets, the duration of the warranty coverage may differ.

©2010 Bombardier Recreational Products Inc., (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. \*\*Ultra-high molecular-weight polyethylene. † Traveling at 50 mph/80.47 km/h (based on BRP Internal test). Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models, accessories or options depicted herein may not be available in your region.

SEA-DOO®

